

### Egebant SanCut 196734

Coating Colour	Black
Liner Colour	Black&White Melange
Liner	Steel Fiber, HPPE, Polyester
Coating	Polyurethane(PU)
Wrist Type	Knit Wrist
Desing	½ Black PU coated melange liner and knit wrist cuff
Thicknees	0,90 mm
Marking	Transfer Print



EN 388:2016



4X42D


### Description

It is produced by applying polyurethane coating on HPPE lining reinforced with stainless steel fiber. It is designed for special applications. While TDM 100 provides D level cut resistance according to ISO 13997 test, it does not compromise fingertip sensitivity. The finger parts of the glove are designed to break easily if caught somewhere.

Usage areas: Surface control applications and special applications.

### Dimensions

Egebant SanCut 196734	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	211	236	241	245	266	270
Hand Length (B) (mm)	151	185	198	203	208	211
Peripheral Length © (mm)	184	193	206	210	220	231
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight /1 Pair (gram)	36,5	40,6	47,2	49,6	55,6	56,1



a= Total Glove Length  
b= Hand Length  
c= Peripheral Length

## EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Yes
EN 388: 2016 +A1: 2018	MNA (2841)	4X42D

## Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	Not Detected
EN 388: 2016 + A1: 2018 A. Tear Resistance	118,60 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	77,24 N

## Speacial Features

Silicon Free	Pending
REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Within Tolerance

## Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

### Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /  
Kocaeli 41420 - Turkey  
T: +90 262 679 1313 E: info@egebant.com.tr