

Egebant SanCut 391734

Coating Colour	Black
Liner Colour	Black&White Melange
Liner	Steel Fiber, HPPE, Polyester
Coating	Nitrile Foam
Wrist Type	Knit Wrist
Desing	½ Black nitrile foam coated melange liner and knit wrist cuff
Thicknees	0,95 mm
Marking	Transfer Printing



EN 388:2016




Description

It is made of nitrile foam coating on an ultra-thin and high gauge HPPE lining reinforced with stainless steel. According to TDM 100 ISO 13997 test it provides a level D. Thanks to high grip micro foam PU coating, comparing to bare-handed working, it makes much easier to hold parts in the hand.

Recommended for: General use, metalworking, assembly and production lines, working with sheet metal, automotive, white goods.

Dimensions

Egebant SanCut 391734	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	200	210	225	235	250	260
Hand Length (B) (mm)	140	150	160	170	180	190
Peripheral Length © (mm)	175	185	195	205	215	225
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight /1 Pair (gram)	49	53	58	59	65	69



a= Total Glove Length
b= Hand Length
c= Peripheral Length

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Yes
EN 388: 2016 +A1: 2018	MNA (2841)	4X44D

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	>8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	16,4N
EN 388: 2016 + A1: 2018 A. Tear Resistance	183,87N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	171,16 N

Speacial Features

Silicon Free	Pending
REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
Sanitized ®	Agreement No:5753.20
DMF Free	Yes

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr