

Egebant SanCut 141745

Coating Colour	Grey
Liner Colour	White & Black Melange
Liner	HPPE, Glass Fiber, Steel Fiber, Polyester and Spandex
Coating	Polyurethane(PU)
Wrist Type	Knit Wrist
Desing	½ Grey PU coated melange liner and knit wrist cuff
Thicknees	1,00 mm
Marking	Transfer Printing



EN 21420

EN 388:2016



4X43E


Description

It is made of polyurethane coating on a durable HPPE lining reinforced with stainless steel and glass fiber. TDM 100 provides E level cut resistance according to ISO 13997 test. It facilitates the holding of dry and low oily parts compared to bare hand grip.

Usage Areas: Metalworking, metal sheet working, production and assembly lines, steel wire applications

Dimensions

Egebant SanCut 141745	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	205	225	235	245	255	265
Hand Length (B) (mm)	135	155	165	175	185	195
Peripheral Length © (mm)	170	190	200	210	220	230
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight /1 Pair (gram)	53	57	63	70	77	80



a= Total Glove Length
b= Hand Length
c= Peripheral Length

EN Test Results

Test	Notified Body / No	Results / Pass
EN 21420:2020	MNA (2841)	Yes
EN 388: 2016 + A1: 2018	MNA (2841)	4X43E

Typical Performance Values

EN 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	26,1 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	237,48 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	110,46 N

Special Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Within Tolerance

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr