

Egebant SanCut 141743

Coating Colour	Grey
Liner Colour	White&Black Melange
Liner	Glass Fiber, HPPE and Polyester and Spandex
Coating	Polyurethane(PU)
Wrist Type	Knit Wrist
Desing	½ Grey PU coated melange liner and knit wrist cuff
Thicknees	1,00 mm
Marking	Transfer Printing



EN 21420

EN 388:2016



4X43C


Description

It is produced from thin and heat resistant HPPE fiber, glass fiber and polyester blend lining. TDM 100 provides C level cut resistance according to ISO 13997 test. It facilitates the holding of dry and low oily parts compared to bare hand grip.

Usage Areas: Metalworking, metal sheet working, production and assembly lines, steel wire applications

Dimensions

Egebant SanCut 141743	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	215	231	232	251	252	271
Hand Length (B) (mm)	158	185	189	189	208	227
Peripheral Length © (mm)	175	180	194	209	210	227
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	48	50	52	61	65	69



a= Total Glove Length
b= Hand Length
c= Peripheral Length

Dimensions and weights can vary by up to 5%

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Yes
EN 388: 2016 + A1: 2018	MNA (2841)	4X43C

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	>8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	11,4 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	324,27 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	100,13 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Within Tolerance

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr

www.egebant.com.tr