


Egebant SanCut 141243

Coating Colour	Grey
Liner Colour	White
Liner	Glass Fiber, HPPE and Polyester and Spandex
Coating	Polyurethane(PU)
Wrist Type	Knit Wrist
Desing	½ Grey PU coated white liner and knit wrist cuff
Thicknees	1,00 mm
Marking	Transfer Printing




Description

It is produced from thin and heat resistant HPPE fiber, glass fiber and polyester blend lining. TDM 100 provides C level cut resistance according to ISO 13997 test. It facilitates the holding of dry and low oily parts compared to bare hand grip.

Usage Areas: Metalworking, metal sheet working, production and assembly lines, steel wire applications

Dimensions

Egebant SanCut 141243	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	215	231	232	251	252	271
Hand Length (B) (mm)	158	185	189	189	208	227
Peripheral Length © (mm)	175	180	194	209	210	227
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	48	50	52	61	65	69



a= Total Glove Length
b= Hand Length
c= Peripheral Length

Dimensions and weights can vary by up to 5%

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Yes
EN 388: 2016 + A1: 2018	MNA (2841)	4X43C

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	>8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	11,4 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	324,27 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	100,13 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Within Tolerance

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr

www.egebant.com.tr