

Egebant SanCut 181743

Coating Colour	Grey
Liner Colour	Blue&White Melange
Liner	Dyneema Diamond & Nylon
Coating	Polyurethane(PU)
Wrist Type	Knit Wrist
Desing	½ Grey PU coated melange liner and knit wrist cuff
Thicknees	0,90 mm
Marking	Transfer Printing



 **Dyneema®**

CE
EN 21420

EN 388

4X43C


Description

It is produced by coating thin Polyurethane (PU) on a cut resistant, light and durable Dyneema Diamond® lining. It does not contain glass fiber and any similar auxiliary fibers. It provides maximum comfort for your skin. While TDM 100 provides C level cut resistance according to ISO 13997 test, it does not compromise fingertip sensitivity. It makes handling dry and less oily parts much easier than working with bare hands.

Usage areas: Assembly and production lines, metalworking, working with metal sheets, steel wire applications.

Dimensions

Egebant SanCut 181743	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	226	240	243	253	260	274
Hand Length (B) (mm)	178	194	198	200	210	220
Peripheral Length © (mm)	166	177	189	197	207	224
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	44	47	53	57	63	66



a= Total Glove Length
b= Hand Length
c= Peripheral Length

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	USB (3038)	Yes
EN 388: 2016 +A1: 2018	USB (3038)	4X43C

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	>8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	13,7 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	197,68 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	106,57 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Within Tolerance

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr

www.egebant.com.tr