

Egebant SanCut 331732

| | |
|----------------|---|
| Coating Colour | Black |
| Liner Colour | Black & White Melange |
| Liner | Glass Fiber, HPPE, Polyester |
| Coating | Nitrile Foam |
| Wrist Type | Knit Wrist |
| Desing | ½ Black nitrile foam coated melange liner and knit wrist cuff |
| Thicknees | 1,00 mm |
| Marking | Transfer Printing |



EN ISO 21420

EN 388



4X41B

EN 407:2020



X1XXXX



Touch Screen Compatible


Description

It is produced by coating Foam Nitrile on a thin and heat resistant HPPE fiber and Polyester blend lining. TDM 100 provides B level cut resistance according to ISO 13997 test. It makes it easier to hold dry and less oily parts compared to holding with bare hands. It is suitable for working with hot parts (100 °C contact temperature) as well as for applications where protection against the risk of cuts is required.

Usage Areas: Metalworking, abrasive work, working with heavy parts, working with sheet metal, production and assembly lines, steel wire applications.

Dimensions

| Egebant SanCut 331732 | Size 6 (XS) | Size 7 (S) | Size 8 (M) | Size 9 (L) | Size 10 (XL) | Size 11 (XXL) |
|-----------------------------|-------------|------------|------------|------------|--------------|---------------|
| Total Glove Length (A) (mm) | 220 | 230 | 240 | 250 | 260 | 280 |
| Hand Length (B) (mm) | 165 | 175 | 185 | 195 | 202 | 206 |
| Peripheral Length © (mm) | 190 | 200 | 210 | 220 | 230 | 235 |
| Over Lock Colour | Brown | Red | Black | White | Blue | Burgundy |
| Glove Weight /1 Pair (gram) | 48 | 52 | 57 | 60 | 66 | 70 |



a= Total Glove Length
b= Hand Length
c= Peripheral Length

EN Test Results

| Test | Notified Body / No | Results / Pass |
|-------------------------|--------------------|----------------|
| EN ISO 21420:2020 | USB (3038) | Yes |
| EN 388: 2016 + A1: 2018 | USB (3038) | 4X41B |
| EN 407:2020 | USB (3038) | X1XXXX |

Typical Performance Values

| | |
|---|-------------|
| EN ISO 21420:2020 | Level 5 |
| EN 388: 2016 + A1: 2018 A. Abrasion Resistance | >8000 Cycle |
| EN 388: 2016 + A1: 2018 A. Blade Cut Resistance | 6,8 N |
| EN 388: 2016 + A1: 2018 A. Tear Resistance | 77,19 N |
| EN 388: 2016 + A1: 2018 A. Puncture Resistance | 49,30 N |

Speacial Features

| | |
|-------------------------|----------------------|
| REACH Regulation | Meet Requirement |
| pH Values | Meet Requirement |
| Azo-colourants and PAHs | Meet Requirement |
| Sanitized ® | Agreement No:5753.20 |
| DMF Free | Yes |

Packaging

| | |
|----------------------|-------------|
| Pairs Per Poly Bag | 10 |
| Poly Bags Per Carton | 6 |
| Carton Count | 60 |
| Carton Dimensions | 600X260X180 |
| Pallet Dimensions | 156X80X120 |

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr