

Egebant SanCut 301735T

Coating Colour	Black
Liner Colour	Black-White & Yellow Melange
Liner	Steel Fiber, HPPE, Polyester, Cotton
Coating	Foam Nitrile
Wrist Type	Knit Wrist
Desing	½ Black Foam Nitrile coated; Thumb Crotch; melange liner and knit wrist cuff
Thicknees	1,35 mm
Marking	Transfer Printing



EN 21420

EN 388



4X21E

EN 407



X1XXXX


Description

It is produced by coating Foam Nitrile on a cut, abrasion and heat-resistant, HPPE fiber and polyester blend lining. Delivers long-lasting performance with reinforced thumb crotch. TDM 100 provides E level cut resistance according to ISO 13997 test. It makes it easier to hold dry and less oily parts compared to holding with bare hands. It is suitable for working with hot parts (100 °C contact temperature) as well as for applications where protection against the risk of cuts is required.

Uses: Metalworking, working with heavy parts, working with sheet metal, production and assembly lines, steel wire applications

Dimensions

Egebant SanCut 301735T	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	205	220	235	245	250	260
Hand Length (B) (mm)	145	155	165	175	185	195
Peripheral Length © (mm)	180	190	200	210	220	230
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	67,71	71,73	78,70	83,42	91,07	95,80



a= Total Glove Length
b=Hand Length
c=Peripheral Length

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Pass
EN 388: 2016 + A1: 2018	MNA (2841)	4X21E
EN 407:2020	MNA (2841)	X1XXXX

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	22,5 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	45,46 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	44,46 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
Sanitized ®	Agreement No:5753.20
DMF Free	Yes

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr

www.egebant.com.tr