egebant®
Sustainable Solutions

SanCut 331334

Egebant SanCut 331334

Coating Colour	Black
Liner Colour	Black
Liner	Steel Fiber, HPPE, Polyester
Coating	Nitrile Foam
Wrist Type	Knit Wirst
Desing	½ Black nitrile foam coated black liner and knit wirst cuff
Thicknees	1,00 mm
Marking	Transfer Printing



Sanitized

CE
EN 21420

EN 388
4X42D

EN 407
X1XXXX

Touch Screen Compatible

Description

It is produced by coating Foam Nitrile on a thin and heat resistant HPPE fiber and Polyester blend lining. TDM 100 provides D level cut resistance according to ISO 13997 test. It makes it easier to hold dry and less oily parts compared to holding with bare hands. It is suitable for working with hot parts (100 °C contact temperature) as well as for applications where protection against the risk of cuts is required.

Usage Areas: Metalworking, abrasive work, working with heavy parts, working with sheet metal, production and assembly lines, steel wire applications.

Dimensions

Egebant SanCut 331334	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	220	230	240	250	260	280
Hand Length (B) (mm)	165	175	185	195	202	206
Peripheral Length © (mm)	195	200	210	220	230	235
Over Lock Colour	Brown	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	48	52	57	60	66	70



a= Total Glove Length
b= Hand Length
c= Peripheral Length

Dimensions and weights can vary by up to 5%

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	MNA (2841)	Yes
EN 388: 2016 +A1: 2018	MNA (2841)	4X42D
EN 407:2020	MNA (2841)	X1XXXX

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	>8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	19,3 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	102,61 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	77,06 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
Sanitized ®	Agreement No:5753.20
DMF Free	Yes

Packaging

Pairs Per Poly Bag	10
Poly Bags Per Carton	6
Carton Count	60
Carton Dimensions	600X260X180
Pallet Dimensions	156X80X120

Head Office
A: N:23, TOSB 3. St. Şekerpınar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr