TAPE CATALOG

tape®

egebant®

www.egebant.com.tr

Rich Heritage, **Strong Future**

Since **1969**

+**57** Years of Experience

+**50** Sales Specialists

+**75** Dealer Network

2 Manufacturing Plants

1 R&D Center

Total Employees +**650**

egebant
Kocaeli
Headquarter and **Factory**

egebant
Şanlıurfa **Factory**



egebant
Global Export **Network**



3+ Continents **30** Countries

Şanlıurfa Factory



Kocaeli Factory & Head Office



ABOUT US

Egebant was established in Karaköy in 1969. With its sustainable solutions, Egebant prioritises customer satisfaction at the highest level and aims to be the permanent solution partner of its customers and stakeholders. In line with this mission, it has been collaborating with globally recognised brands for many years.

Accordingly, Egebant brings the products of globally strong brands such as 3M, Klingspor, Dynabrade, and Sicad to the Turkish market.

Guided by its core values of trustworthiness, innovation, sincerity, courage, and participation, Egebant builds long-term, trust-based relationships with its customers and stakeholders while developing flexible, tailored solutions for them.

By leveraging its manufacturing experience, which it has gained through providing services to many industry-leading brands—from the automotive sector to home appliances—Egebant continues to expand its product range with its brands, Egebant and Sander, while making investments in line with market needs.

With over 650 employees, more than 50 active sales specialists, and a widespread dealer network across Turkey, Egebant operates manufacturing facilities in Şekerpınar, Kocaeli, and Şanlıurfa. The company exports to more than 30 countries across three continents, primarily in Europe, offering a diverse range of products for various industries.

Through its customer-centric approach, Egebant conducts research and development (R&D) activities to create innovative solutions that generate value for all its customers and stakeholders.

As part of its environmental policy, Egebant effectively manages the inputs of its production processes and energy resources, developing methods to increase energy efficiency, reduce waste, and prevent pollution.

With a commitment to environmental sustainability, the company has launched a Zero Waste Project in its facilities, ensuring waste separation at the source to minimise environmental risks. Additionally, Egebant is expanding its expertise in green energy through its recycling facilities.

Moreover, to contribute to the reduction of emissions and the development of a renewable energy system, Egebant plans to generate a significant portion of the energy it consumes at its Şanlıurfa production facility through a rooftop solar power plant.

For 56 years, Egebant has been successfully growing its brands and reputation with the vision of becoming a global leader, continuously producing sustainable solutions and creating lasting value for all its stakeholders.

Finding the Right Gloves is

Now Effortless!

Easily find the gloves you are looking for by using the Glove Selector on **egebant.com.tr**, powered by an algorithm that simplifies glove selection for various industries and needs.

The best protection is in your hands with the fastest selection!



1. Scan the QR code
2. Select the Filters You Want!
3. View the Gloves That Match Your Needs



SCAN THE QR CODE

TABLE OF CONTENTS

Adhesive Tapes

Adhesive Tapes 8
Masking Tapes..... 9
Duct Tapes..... 10
Strapping Tapes.....11
Filament Tapes 12
Aluminium Tapes 13
Double Sided Tapes 54
Film Backing Tapes 15
Foam Tapes..... 16
Pe Freezer Tapes 17
Refrigerator Back Carton Plates..... 58

ADHESIVE TAPES



www.egebant.com.tr

Adhesive Tapes

Product Features

- General purpose packaging tape.
- It is suitable for light and medium weight carton closure.
- Suitable for use with handheld dispenser and automatic packaging machines
- Can be produced at any desired width and length



Product Code	Carrier	Adhesive Type	Colour	Thickness	Elongation (%)	Temperature Resistance (°C)	Application Areas
Sander PP5231	BOPP	Synthetic Rubber	Transparent / Brown / White	25 mic.	% 145	60 °C	General purpose packaging tape.
Egebant PP31	BOPP	Synthetic Rubber	Transparent / Brown / White	28 mic.	% 145	60 °C	General purpose packaging tape.
Egebant PP30S	BOPP	Natural Rubber	Transparent / Brown / White	28 mic.	% 145	60 °C	General purpose packaging tape.
Egebant PP35	BOPP	Natural Rubber	Transparent / Brown / White	35 mic.	% 145	60 °C	General purpose packaging tape.
Egebant PVC 330	PVC	Natural Rubber	Transparent / Brown / White	33 mic.	% 145	60 °C	General purpose packaging tape.
Egebant Kraft Tape	Kraft Non Woven	Natural Rubber	Brown	105 mic.	% 6	60 °C	General purpose packaging tape.



Masking Tapes

Product Features

- Can be removed without leaving a residue
- Solvent-resistant
- Temperature resistance
- Easy tear
- Controlled expansion
- Conformability to stretch and adhere round curves
- High initial adhesion



Product Code	Carrier	Adhesive Type	Thickness	Temperature Resistance (°C)	Application Areas
Sander 6127	Crepe Paper	Natural Rubber	110 mic.	30 °C	General purpose masking tape. Construction industry, automotive industry, white goods sector and cable bundling.
Egebant MSK60	Crepe Paper	Natural Rubber	125 mic.	80 (30 °C)	General purpose masking tape. Construction industry, automotive industry, white goods sector and cable bundling.
Egebant MSK6280	Crepe Paper	Natural Rubber	130 mic.	100 (30 °C)	High heat resistance, wet sanding and tiner-like chemical resistance, a general purpose masking tape. Up to 100 degree heat resistance.
Egebant MSK100	Waterproof Crepe Paper	Natural Rubber	140 mic.	120 (30 °C)	General purpose masking tape. Very high heat resistance, resistant to wet sanding and filling materials, thinner infrared light, durable and resistant to chemicals. Up to 120 degrees heat resistance
Egebant P40	PET	Silicon	60 mic.	180 (30 °C)	High-Temperature powder paint masking tape.
Egebant 6268	Crepe Green Paper	Natural Rubber	125 mic.	80 (30 °C)	General purpose masking tape. Construction industry, automotive industry, white goods sector and cable bundling.
Egebant 6265	Blue Crepe Paper	Natural Rubber	125 mic.	80 (30 °C)	General purpose masking tape. Construction industry, automotive industry, white goods sector and cable bundling.
Egebant 6267	Orange Crepe Paper	Natural Rubber	125 mic.	80 (30 °C)	General purpose masking tape. Construction industry, automotive industry, white goods sector and cable bundling.
Maskopri	Paper / HDPE Film	Natural Rubber	125 mic.	80 (30 °C)	The film is electrostatically loaded to stick to whole surface. Recommended for professional, industrial and DIY applications.

Duct Tapes

Product Features

- Hand-tearable
- Moisture resistant
- Can adhere to most surfaces
- High tensile strength
- Waterproof, suitable for many repair applications.



Product Code	Carrier	Adhesive Type	Colour	Thickness	Elongation (%)	Temperature Resistance (°C)	Application Areas
Egebant TPL201	PE Coated Cloth	Synthetic Rubber	Black / White / Grey	180 mic.	% 10	60 °C	It is a general purpose cloth tape.
Egebant TPL204	PE Coated Cloth	Synthetic Rubber	Grey	155 mic.	% 13	60 °C	It is a multi-purpose, single-sided repair tape.
Egebant CT1604	PE Coated Cloth	Synthetic Rubber	Grey	160 mic.	% 10	60 °C	It is a general purpose cloth tape.

Strapping Tapes

Product Features

- No residue left on the surface after sticking.
- Used for strapping plastic and metal parts in White Goods Industry.
- High UV resistance.



Product Code	Carrier	Adhesive Type	Colour	Thickness	Temperature Resistance (°C)	Application Areas
Egebant PP550	MOPP	Natural Rubber	Blue / White	55 mic.	60 °C	General-purpose strapping tape.
Egebant PP505	MOPP	Natural Rubber	White	70 mic	60 °C	General-purpose strapping tape.
Egebant PP850	MOPP	Natural Rubber	Blue / White	113 mic.	60 °C	General-purpose strapping tape.
Egebant PP855	MOPP	Natural Rubber	Blue	113 mic.	60 °C	General-purpose strapping tape.

Filament Tapes

Product Features

Reinforced with glass fiber packaging and bundling tape.



Product Code	Carrier	Adhesive Type	Colour	Thickness	Elongation (%)	Temperature Resistance (°C)	Application Areas
Egebant FG10	Reinforced with fiberglass BOPP	Synthetic Rubber	Clear / White	120 mic.		60 °C	It is a flat-woven palletizing belt.
Egebant FGBD	Reinforced with fiberglass BOPP	Synthetic Rubber	Clear / White	120 mic.		60 °C	It is a cross-woven palletizing belt.
Egebant ST300	MOPP	Synthetic Rubber	Clear	50 mic.		60 °C	It is used as a conveyor belt in food and beverage packaging.
Egebant GL96	Fiberglass	Silicon	White	165 mic.	% 3,5	250 °C	It is a high-temperature resistant fiberglass cloth tape, reinforced on one side.

Aluminium Tapes

Product Features

- High resistance to moisture and chemicals
- Thermal conductivity
- Heat and light reflectance
- Flame resistance
- Strength of the external environment
- Vibration damping and isolation



Product Code	Carrier	Adhesive Type	Colour	Thickness	Tensile Strength	Temperature Resistance (°C)	Application Areas
Egebant AF1825	Al.Foil	Acrylic	Metallic Gray	18 mic.	40	150 °C	General purpose insulation applications
Egebant AF3025	Al.Foil	Acrylic	Metallic Gray	30 mic.	40	150 °C	General purpose insulation applications
Egebant AF4025	Al.Foil	Acrylic	Metallic Gray	40 mic.	40	150 °C	General purpose insulation applications
Egebant AF5025	Al.Foil	Acrylic	Metallic Gray	50 mic.	40	150 °C	General purpose insulation applications
Egebant AF7525	Al.Foil	Acrylic	Metallic Gray	75 mic.	60	150 °C	General purpose insulation applications
Egebant TT9934	Al.Foil	Acrylic	Metallic Gray	150 mic.	275	150 °C	General purpose insulation applications
Egebant TT9940	BOPP - Al.Foil	Acrylic	Metallic Gray	90 mic.	105	150 °C	It is a BOPP coated adhesive aluminium tape having high tensile strenght. Used in white goods sector and aluminium panels bonding.
Egebant AF5025 WL	Al.Foil	Acrylic	Metallic Gray	90 mic.	40	120 °C	HVAC

Double Sided Tapes

General Properties

- High initial adhesion
- Easy to tear by hand
- Designed to bond to low surface energy plastic



Product Code	Carrier	Adhesive Type	Colour	Thickness	Temperature Resistance (°C)	Application Areas
Egebant TNT710	Non Woven	Synthetic Rubber	Translucent	100	60 °C	Usually laminated foam operations, cardboard, metal and adding used.
Egebant D022A	Non Woven	Acrylic	Translucent	100	120 °C	For general purposes, wood, metal, glass, paper, plastic used for welding
Egebant 6750	Non Woven	Acrylic	Blue	100	200 °C	Has a high initial adhesive strength and high-speed coil Adding used
Egebant TNT710/160	Non Woven	Synthetic Rubber	Translucent	160	60 °C	Laminated foam operations, cardboard and general purpose
Egebant VX160	Non Woven	Synthetic Rubber	Translucent	160	60 °C	Laminated foam operations, cardboard and general purpose
Egebant 90HX	None	Acrylic	Translucent	110	90 °C	Cross Linked Transfer Tape

Film Backing Tapes

Product Features

- Ease of use
- PVC, PET, cloth, fabric and OPP carriers
- Kinds of acrylic and rubber adhesive
- High and low surface energy good adhesion to the product
- High initial adhesion force



Product Code	Carrier	Adhesive Type	Colour	Thickness	Temperature Resistance (°C)	Application Areas
Egebant RDA700	OPP	Synthetic Rubber	Clear	98	60 °C	General purpose
Egebant PT150	PET	Modified Acrylic	Clear	150	120 °C	Bonding of metal panels and mirrors
Egebant PT205	PET	Modified Acrylic	Clear	205	120 °C	Bonding of metal panels and mirrors
Egebant D5082	PET	Acrylic	Clear	100	90 °C	General purpose
Egebant D5028	PET	Acrylic	Clear	125	90 °C	General purpose
Egebant D2040	PET	Acrylic	Clear	95	90 °C	General purpose

Foam Tapes

Product Features

- Flexibility and space-filling
- Bonding rough or irregular surfaces
- Vibration and noise isolation
- Impact resistance
- Heat resistance



Product Code	Carrier	Adhesive Type	Colour	Thickness (mm)	Temperature Resistance (°C)	Application Areas
Egebant FT 67	PE Foam	Acrylic	White	1,0	90 °C	General purpose bonding solutions used in outdoor environments.
Egebant FT 67	PE Foam	Acrylic	Black	1,0	90 °C	General purpose bonding solutions used in outdoor environments.
Egebant 1100R+	Acryled Foam	Acrylic	White	1,1	120 °C	General purpose bonding solutions used in outdoor environments.
Egebant 71100	Acryled Foam	Acrylic	Black / White	1,1	120 °C	General purpose bonding solutions used in outdoor environments.
Egebant 640R+	Acryled Foam	Acrylic	White	0,64	120 °C	General purpose bonding solutions used in outdoor environments.
Egebant 70080	Acryled Foam	Acrylic	Black / Grey	0,8	120 °C	General purpose bonding solutions used in outdoor environments.
Egebant 500R	Acryled Foam	Acrylic	Clear	0,5	120 °C	General purpose bonding solutions used in outdoor environments.
Egebant 1000R	Acryled Foam	Acrylic	Clear	1,0	120 °C	General purpose bonding solutions used in outdoor environments.

Pe Freezer Tapes




Product Code	Carrier	Adhesive Type	Colour	Thickness	Tensile Strenght	Adhesive N/25mm	Application Areas
Egebant TT6405	LDPE	Synthetic Rubber	White	73 mic.	28	13	Used in Evap coil winding in white goods industry. Polyurethane has a high binding capacity. Strong resistance against cold.
Egebant TT6400	LDPE	Synthetic Rubber	White	85 mic.	30	20	Used in Evap coil winding in white goods industry. Polyurethane has a high binding capacity. Strong resistance against cold.

Isolation Plate


Product Features


Adhesive laminated Policarbonate or PVC plates, to isolate electronic components, in electronic devices.













Refrigerator Back Carton Plates







Product Features


- Aluminium and PE laminated carton for refrigerator back panels.
- Can be converted indifferent dimensions and shapes.


Frameless Tapes




Product Features

- Adhesive laminated Polyurethane or Silicone strips for TV production.
- Different friction and shore levels
- Can be converted into different lengths and widths.








Die-Cut Kiss-Cut Product

Product Features

Adhesive laminated foams. Die cut, kiss cut, double sided tape, Aluminium Tapes.



Notes

egebant®

www.egebant.com.tr

egebant®

Headquarter
TOSB 3. Cadde No: 23, Postal Code: 41420,
Sekerpinar, Cayirova / Kocaeli, Turkey
T: +90 262 679 1313
F: +90 262 679 1300
E: info@egebant.com.tr

www.egebant.com.tr

/egebant /egebantcom /Egebant /Egebant /EgebantComTr